


OVAKO

THE SAFE CHOICE FOR SUB-ZERO PERFORMANCE

SZ-STEEL®



SAFETY COMES IN MANY SHAPES AND SIZES

Arctic pipeline bolts. Hydraulic parts. Offshore lifting devices. When the temperature drops, steel parts need to rise to the occasion with safe and reliable performance around the clock. There is no room for brittle fracturing or cracking. The price of human safety and environmental risks is simply too high.

Some of our most demanding customers tell us that safety in cold climates is increasingly becoming an urgent priority. Many are under pressure to comply with demanding oil and gas or shipbuilding standards. Nobody wants to see an accident or unscheduled maintenance when temperatures drop to -40°C and below.

Extreme sub-zero performance

So how do you know whether the quenched and tempered bar or tube you've been using for years can withstand -60°C? Or what about -100°C? And what about those ISO, EN, ASTM, DIN and JIS certification requests in the process of meeting API, DNV and other standards for the fabrication of steels with guaranteed impact and toughness properties at low temperatures?

SZ-Steel for cold climate

This is where SZ-Steel can help. The abbreviation SZ, which means sub-zero, refers to "cold climate" steels that are proven to retain their material properties at -40°C in relation to size and yield. Many are tested to withstand temperatures down to -100°C and beyond.

How can we serve you?

Although we can't legally guarantee fabricated parts, we can ensure that SZ-Steel will retain the favorable properties you need. Our service team can also advise you on application suitability, mechanical data, materials supply and logistics. All to live up to our promise that SZ-Steel is the "safe choice for sub-zero performance."


SZ-STEEL BENEFITS Enables the application of high-strength solutions at sub-zero temperatures. • Enables design that creates safety for workers, service crews and the environment. Retains key material properties and offers reduced risk of embrittlement and fracturing. • Meets key global safety standards.



HARNESS THE HEAT...

Can heat defeat cold? Yes, it can. Although it might sound somewhat counter-intuitive, sub-zero safety starts with the right metallurgy, the right heat treatment and the right control over steel microstructure. It's a delicate balancing act between ductility and strength. Wrong heat treatment and you end up with a hard material that could risk brittle fracturing. Too ductile a material and you may not have the high strength required. Low impurity levels and controlled grain size give the edge you need.

...TO THRIVE IN THE COLD It's a simple fact that cold temperatures complicate a washers and other key parts have a tendency to become steel's ability to remain ductile under heavy loads and embrittled and shatter at just the wrong times. With stress. Whether it's a pressure valve, hydraulic tube or human lives and the environment at stake, skimping on connector, you want a material that remains ductile at costs or materials is simply not an option. sub-zero temperatures. Sadly, threaded fasteners, nuts, 04 / 05



IMAGINE LIFE AT -101°C. OUR STEELS DO.

We can't help ourselves. As curious steelmakers, we're always asking questions. Like what happens to a 200-millimeter-thick round bar at -101°C? Would it shatter upon impact? How would the mechanical strength, impact resistance and ductility be affected? To find out, we invented one of the world's toughest sub-zero tests for engineering steels.

Actually, the whole point of creating the Ovako Big Freeze Test Facility was not just to satisfy our own curiosity. We wanted to provide customers with empirical evidence that our steels hold their beneficial properties in extreme cold. We wanted to base our claims on fact rather than extrapolations or simply referring to our "zero-complaints" track record. Sure, that's all fine, but nothing beats the persuasive power of an experiment that is verified against industry standards.

Located in Imatra, Finland

So we set up our own sub-zero test facility at our Ovako Imatra Steel mill in southeast Finland near the Russian border. Is this unusual? Yes. Unlike other cold test facilities within Ovako, this one would test our low-alloy bar at -101°C using cryogenic liquid nitrogen and methanol as a cooling media. It had never been done before. At such temperatures, even some of the best materials become brittle and fall apart.

Charpy V-notch testing

After immersing steel parts in the Freeze Box, we then take them out and apply the Charpy V-notch test, a standardized high-strain test to determine the amount of energy absorbed by a material during fracture. If the material breaks on a flat plane, the fracture is regarded as brittle, and if the material breaks with jagged edges or shear lips, then the facture is considered to be ductile.

Meeting global standards

The results are then measured in accordance with the Standard Methods for Notched Bar Impact Testing of Metallic Materials, as specified by ASTM E23, ISO 148-1 or EN 10045-1. Needless to say, the results were superior. But more than just providing us with "bragging material," they serve as a basis for guiding our customers to choose the right materials for axles, bolts, gear wheels, connectors and other steel parts.

FREEZING OUT RISK IN REMOTE LOCATIONS

Risk. It's a nasty word. Especially in remote workplaces where sudden impacts can affect the safety and reliability of steel components at sub-zero temperatures. Personal injury and operational downtime are just too costly to be left to chance.

The problem is that steel tends to become brittle and susceptible to cracking at low temperatures and under high pressure or torque. In other words, the performance you need may decline in cold climates. That is, unless you're using SZ-Steel.

Critical components

One customer that turned to us is ABB Oy Motors and Generators Helsinki, a leading supplier of power equipment to industries working in extreme conditions. For many years, the company has been sourcing SZ-Steel for their rotor shafts, one of the most critical components in their electric motors.

Designed for -55°C

Why Ovako steel? Because the rotor shafts are critical to the reliability of the electric motors in extreme conditions, including in sub-zero temperatures. Normal working conditions for ABB motors range between -20°C and +20°C, but they are designed to plunge as low as -55°C.

Demanding customers

Together, the shaft and rotor serve as the backbone of ABB's AC motors, delivering the mechanical power that drives the winches, compressors, conveyor belts and milling machines that, in turn, support the mining and oil and gas operations safely and reliably. In other words, failure is not an option.



Certain ABB motors, whether variable speed drive (VSD) or direct online (DOL), boast rotors with heads weighing up to 130 tons and spanning four to eight meters in length. Enormous torque loads in cold conditions are brought to bear on the Ovakosourced shafts throughout their speed range.



YOUR LIFELINE FOR SAFE LIFTING OFFSHORE

High winds. Rough seas. Sub-zero temperatures. Not exactly the optimal conditions for lifting heavy containers from a ship's deck or oil platform. Yet this is the typical environment faced by offshore crews in the energy sector every day, placing a constant test on safe and strong materials.

For many years, Ovako has been providing bar, ring and other products to the offshore energy sector. Customers use our steel for sub-zero applications ranging from the hydraulic cylinders in windmills to anchor chains. Their components need to withstand high shock loads and fatigue on the high seas.

Exceeding tough DNV requirements

Supplying many of these offshore players is Gunnebo Industries, a leading global manufacturer of lifting and lashing equipment, which uses SZ-Steel. Their chain or wire rope slings, shackles and master links are then sold in compliance with DNV (Det Norske Veritas) 2.7-1 certification, meaning that they're approved to function safely in cold climates. Gunnebo Industries prides itself on certifying their products to perform down to -40°C and lower.

No inclusions, excellent documentation

To achieve this, they place very specific demands on the chemical composition and heat treatment process used by Ovako for its SZ-Steel. Such requirements include the level of non-metallic inclusions, grain size and impurity levels.

Detailed and helpful documentation

The details of each heat treatment are included in mill certification tests that Ovako delivers to Gunnebo Industries, providing traceability and assurance about the steel quality and process. The certification includes the results of tests that measure the heat's toughness, tensile strength, elongation and hardness.



UNMATCHED QUALITY UNSTOPPABLE STRENGTH

Designing and manufacturing hydraulic cylinders and other steel parts to handle heavy loads is certainly a challenge. Making sure they retain their favorable properties under stress at sub-zero temperatures is quite another matter.

Take the case of a major wind turbine manufacturer that needed a steel grade for piston rods. These are used in the "pitch" cylinder to provide strength in all directions and set the angle of the blades. After evaluating several options, they chose our Ovako 280N Cromax steel since it meets minimum 27J at -40°C when impact tested.

Pouring concrete in the cold

Yet another example is a manufacturer of concrete pumping equipment for construction sites. Since the end of an articulated delivery boom can often extend dozens of

meters from the pump location at considerable height, it increases the gravitational pull and stress on the cylinders. This, in turn, increases the risk of malfunction, human injury and property damage. In short, the equipment's ability to securely and effectively deliver the concrete pour, even in temperatures as low as -20°C, is critical. According to the subcontractor providing hydraulic cylinders for these systems, it was a logical choice to use SZ-Steel since the characteristics of our tube exceeded their sub-zero requirements by more than 100%.



SZ-Steel combined with IQ-Steel

For concrete pumping and other applications, hydraulic cylinders are critical components that must stand up to a three-dimensional load. This means they must be able to handle high levels of impact strength in both the longitudinal and transverse direction. It is not uncommon for steels with normal levels of sulphur and other nonmetallic inclusions to show excellent impact strength in the longitudinal direction, while the transverse impact strength is dramatically lower. This is clearly a detrimental factor for a three-dimensionally loaded component such as hydraulic cylinders.

Handling loads in all directions

However, the ability to handle loads in all directions is sometimes overlooked since most standards only specify impact strength in the longitudinal direction. By combining the properties of our SZ-Steel with the isotropic properties of our IQ-Steel, we ensure a very high level of strength in the transverse direction as well. See the following graph showing SZ-Steel 277L with a normal sulphur level versus SZ-Steel 277Q with IQ-treatment.

Impact toughness





"We've enjoyed a very good relationship with Ovako because they understand exactly what is required from our customer. They meet all the specifications and because they have stocking capabilities nearby they can deliver quickly and in low as well as high volumes."

> **Mr. Jürgen Hahn** Klingel Hydraulik Gmbh

WE MEET API AND OTHER STANDARDS BUT THE TOUGHEST ONE IS YOURS

No matter how many "certificates of approval" we mount in our reception areas (and there are many), you're likely to shrug. The fact is that most of our customers have needs that go beyond the obvious: unique delivery demands; special formats; or they just want someone to talk to who actually understands their needs.

If you've been in the steel business as long as we have (read: 400 years), you're fully aware that technical specifications are one thing and reality is another. Many steel suppliers are good at ticking off all the boxes, but lack the depth of expertise needed to combine metallurgical insight with practical advice. Nor can they provide you with a direct line into their mills for traceability, quality questions, service and more.

Demanding sub-zero requirements

But let's start with technical specs. When it comes to subzero steels in demanding industries like shipbuilding, offshore oil and gas and others, we understand the scope. Many of our SZ-Steel grades are tested to meet demanding sub-zero fabrication requirements such as the DNV offshore standards and other international standards.

Bolts, fasteners and fittings

When it comes to sub-zero steel bolting materials, we're required to follow ASTM A320 L7 standards as well. This includes steel bolting materials for pressure vessels, flanges and fittings for low-temperature service. The list goes on, particularly when it comes to the demanding American Petroleum Institute (API) standards, which are on everyone's minds.

Coming back to you

Beyond all the standards, we always come back to you and your specific needs. How can we help you reduce maintenance costs? Improve service? This might involve everything from providing full technical advice on application suitability, mechanical data, batch production, material supply and logistics.

"The arctic environment is extremely sensitive but also recognized for its extensive resource potential, so all measures to reduce environmental and safety risks and protect this important

Magnus Friberg Northern Europe Area Technical Manager, Lloyd's Register Quality Assurance



WE DON'T HAVE POLAR BEARS BUT NOT FAR FROM IT

OVAKO HOFORS-HÄLLEFORS

Premium-quality steel products of high cleanliness and fatigue strength. Used primarily for components in bearings, diesel engines, oil & gas, mining and other special products. New ring mill for bearing steel and other demanding applications.

One of our experts in cold-climate steels made the comment: "We don't need an attitude to be cool – nine months of the year we have no choice." It made us chuckle, but we also realized it was more than true. Perched on the northern rim of Europe and located close to the Arctic Circle, we have our origins in a "cold" steelmaking tradition that dates back more than 400 years.

You could say that working safely in cold environments is in our DNA. In fact, we expect nothing less from our products, especially for the oil and gas, shipbuilding and other demanding industries. And while we may not have the world record of -89.2°C (Antarctica), we have witnessed temperatures dip to -51.4°C in Kittilä, Finland (Lapland) and -53.0°C in Malgovik, Sweden. Even the polar bears were keeping away those days.

COUNTRY / REGION	TEMPERATURE	TOWN / LOCATION	DATE
Antarctica*	-89.2°C (-128.6°F)	Vostok Station	1983-07-21
Russia	-68°C (-90°F)	Verkhoyansk and Oymyakon, both in Sakha Republic	1892-02-07
Canada	-63°C (-81°F)	Snag, Yukon	1947-02-03
United States, Alaska	-62°C (-80°F)	Propect Creek, Alaska	1971-01-23
United States, contiguous	-57°C (-70°F)	Rogers Pass, Montana	1954-01-20
Finland	-51.5°C (-60.7°F)	Kittilä, Lapland	1999-01-28
France	-41.0°C (-41.8°F)	Mouthe, Doubs	1985-01-17
Germany	-45.9°C (-50.6°F)	Funtensee, Berchtesgadener Land, Bavaria	2001-12-24
Iceland	-37.9°C (-36.2°F)	Grímsstaoir	1918-01-21
Norway	-51.4°C (-60.5°F)	Karaskjok, Finnmark	1886-01-01
Sweden	-53.0°C (-63.4°F)	Malgovik, Västerbotten County	1941-12-13

^{*} Lowest temperature ever recorded

Source: Compiled from recognized international meteorological bureaus.



WHAT SUB-ZERO STEEL WILL YOU LEAVE OUT IN THE COLD?

We're sometimes asked how our steels perform in the cold. "Will this IQ-Steel maintain its isotropic properties on a pipeline in Alaska at -60°C?" "We love our M-Steel, but can it handle -101°C offshore?" To guide you, we've gathered examples of applications and how our steel measures up to standard – often setting a standard within the standard.

EXAMPLES OF SUB-ZERO STANDARDS FOR DEMANDING APPLICATIONS

Application Area Standards Standard Specifics Strength Strength Impact Strength Direct MPa (min) MPa (min		Standard requirement							
API 6A Spec for Wellhead and Christmas Tree Equipment Temperature classifaction L through V PSL 1 to 4 75K 517 655 -46 20 L API 6D Spec for Pipeline Valves 689 -29 34 L API 16A Spec for Drill-through Equipment Temp Rating T-20 75K 517 655 -29 20 L API 16C Spec for Choke and Kill Systems Temp Rating A, B, P and U 75K 517 655 -29 20 L EN ISO 898-1 Bolts, screws and studs with specified property classes Property class 10.9 940 1040 -20 27 L EN ISO 898-1 Specified Property classes 7 Spec for Mod 440 600 20 60 L ASTM A320 Spec for Bolting for Low-Temperature Grade L7 725 860 -101 27	Sample Direction	Impact Strength							Application
API 6A Christmas Tree Equipment through V PSL 1 to 4 75K 517 655 -46 20 II API 6D Spec for Pipeline Valves 689 -29 34 II API 16A Spec for Drill-through Equipment Temp Rating T-20 75K 517 655 -29 20 II API 16C Spec for Choke and Kill Systems Temp Rating A, B, P and U 75K 517 655 -29 20 II EN ISO 898-1 Bolts, screws and studs with specified property classes Property class 10.9 940 1040 -20 27 II Construction EN 10269 Steels and nickel alloys for fasteners with specified elevated and/or low temperature properties ASTM A320 Spec for Bolting for Low-Temperature Grade L7 725 860 -101 27									Area
API 16A Spec for Drill-through Equipment Temp Rating T-20 75K 517 655 -29 20 L API 16C Spec for Choke and Kill Systems Temp Rating A, B, P and U 75K 517 655 -29 20 L EN ISO 898-1 Bolts, screws and studs with specified property classes Property class 10.9 940 1040 -20 27 L EN 10269 Steels and nickel alloys for fasteners with specified elevated and/or low temperature properties ASTM A320 Spec for Bolting for Low-Temperature Grade L7 725 860 -101 27	L	20	-46	655	517			API 6A	
API 16A Spec for Drill-through Equipment Temp Rating T-20 75K 517 655 -29 20 II API 16C Spec for Choke and Kill Systems Temp Rating A, B, P and U 75K 517 655 -29 20 II EN ISO 898-1 Bolts, screws and studs with specified property classes Property class 10.9 940 1040 -20 27 II Construction EN 10269 Steels and nickel alloys for fasteners with specified elevated and/or low temperature properties ASTM A320 Spec for Bolting for Low-Temperature Grade L7 725 860 -101 27	L	34	-29	689			Spec for Pipeline Valves	API 6D	
EN ISO 898-1 Bolts, screws and studs with specified property classes Property class 10.9 940 1040 -20 27 II Construction EN 10269 Steels and nickel alloys for fasteners with specified elevated and/or low temperature properties ASTM A320 Spec for Bolting for Low-Temperature Grade L7 725 860 -101 27	L	20	-29	655	517	Temp Rating T-20 75K	Spec for Drill-through Equipment	API 16A	Oil & Gas
Construction Steels and nickel alloys for fasteners with specified elevated and/or low temperature properties ASTM A320 Spec for Bolting for Low-Temperature Service Grade L7 725 860 -101 27	L	20	-29	655	517		Spec for Choke and Kill Systems	API 16C	
EN 10269 Steels and nickel alloys for fasteners with specified elevated and/or low temperature properties ASTM A320 Spec for Bolting for Low-Temperature Grade L7 725 860 -101 27 EN 13201 3.1 Cranes General Design - Limit States and Cape 315 400 40 327 Limit States and Cape 315 400 400 400 327 Limit States and Cape 315 400 400 400 327 Limit States and Cape 315 400 400 400 327 Limit States and Cape 315 400 400 400 327 Limit States and Cape 315 400 400 400 327 Limit States and Cape 315 400 400 400 400 400 400 400 400 400 40	L	27	-20	1040	940	Property class 10.9		EN ISO 898-1	
EN 10269 Steels and nickel alloys for fasteners with specified elevated and/or low temperature properties ASTM A320 Spec for Bolting for Low-Temperature Grade L7 725 860 -101 27 EN 12001 2.1 Cranes General Design - Limit States and Captal Additional Captal Additional Captal Ca									
EN 10269 Steels and nickel alloys for fasteners with specified elevated and/or low temperature properties ASTM A320 Spec for Bolting for Low-Temperature Grade L7 725 860 -101 27 EN 12001 2.1 Cranes General Design - Limit States and Captal Additional Captal Additional Captal Ca									
EN 10269 with specified elevated and/or low temperature properties ASTM A320 Spec for Bolting for Low-Temperature Grade L7 725 860 -101 27 EN 13001 3.1 Cranes General Design - Limit States and Case 345 400 40 37									Construction
ASTM A320 Service Grade L7 725 860 -101 27	L	60	20	600	440	25CrMo4	with specified elevated and/or low	EN 10269	
EN 13001-3-1 Cranes General Design - Limit States and		27	-101	860	725	Grade L7		ASTM A320	
proof competence of steel structures 3555 515 490 -40 27 1	L	27	-40	490	315	S355	Cranes General Design - Limit States and proof competence of steel structures	EN 13001-3-1	
Mobile cranes									Mobile cranes
Steels for wolded round link chains and	L	60	20	1180	1060	23MnNiMoCr5-4		EN 17115	&
									LITTING devices

CHOOSE FROM MANY SHAPES AND FORMS

Demanding customers all over the world rely on Ovako to deliver safe and reliable steel in a wide range of shapes and forms. Our products are therefore characterized by durability, uniformity, close tolerances and small machining allowances. Our rigorous quality control ensures our products are consistent from batch to batch and easy to process further. This simplifies manufacturers' production processes and helps to reduce costs.



FORGED BAR

Square forged bar in dimensions 200 – 400 mm. Round forged bar in dimensions 220 – 350 mm. Dimensions outside these ranges can be provided upon agreement.



HOT ROLLED BAR

Available in a wide range of sizes from 14 – 200 mm. Characterized by close tolerances and excellent dimensional properties and surfaces.

EXAMPLES OF HOW SZ-STEEL MEASURES UP TO STANDARD

			Exampels Ovako	of suitable Typical data of Ovako grades **							
	Application	Examples of Standards	Ovako Grade	Corresponding Standard *	Yield Strength	Tensile Strength	Impact Strength		Sample Direction	Products	Max. Dia/wall (mm)
	Area				MPa	MPa	Temp (C)	Joule			
		API 6A	Ovako 326C	AISI 4140	600	740	-50	150	L	Bars, Tubes, Rolled rings	
		API 6D	Ovako 281T	19MNV5	620	740	-40	115	L	Rolled rings	
	Oil & Gas	API 16A	Ovako 322D	AISI 4130	620	730	-50	100	L	Bars, Tubes, Rolled rings	
		API 16C	Ovako 322D or 322Q	AISI 4130	620	730	-50	100	L	Tubes	
	Construction	EN ISO 898-1	Cromobolt	42CrMo6 F	980	1100	-40	40	L	Bars	60
			ImacroM	5Cr16F	980	1100	-55	40	L	Bars	60
			SB27M12CB	27MnCrB5-2	1000	1070	-40	85	L	Bars	35
			SB30M12CB	30MnCrB5-2F	1030	1090	-40	65	L	Bars	42
			SB29M10CB		1050	1100	-40	55	L	Bars	50
		EN 10269	25CrMo4		460	650	-40	120	L	Bars	100
		ASTM A320	Imatra L7		970	1085	-101	27	L	Bars	30
		EN 13001-3-1	520M		400	520	-40	27	L	Bars	100
	No della succession										
	Mobile cranes & Lifting devices	EN 17115	23MnNiMoCr54	23MnNiMoCr5-4	1100	1200	-40	50	L	Bars	70
			Ovako 277 L		660	800	-40	110	L	Bars, Tubes, Rolled rings	160
			Ovako 277Q		660	800	-40	90	Т	Bars, Tubes, Rolled rings	120

^{*} Designation followed by "F" is not a formal standard grade but named according to the rales of EN10027. ** Typical data are not guaranteed.



COLD-WORKED BAR

Ovako's peeled bar in optional sizes in the 20 – 195 mm diameter range. Ovako's drawn bar in the 11 – 55 mm diameter range. Ovako's ground bar in the 12 – 100 mm diameter range.



HARD-CHROMED AND NICKEL-PLATED BAR

Cromax is Ovako's brand for hard-chrome plated bars and tubes. Nikrom is the name for Ovako's nickel-plated bars.



SEAMLESS TUBES

Tubes are available in hot-rolled or coldworked condition. Produced in sizes between 30 – 245 mm OD and possible to have cut to part length.



STEEL GRADES AND HEAT TREATMENT

A large number of steel grades and a menu of heat-treatment processes are available to meet your demands.



PRE-COMPONENTS

Going for pre-machined components allows customers to minimize stockholding, crosscutting and machining.



ROLLED AND FORGED RINGS

Cylindrical, profiled or machined rings with geometry close to the final shape of the product. Full dimensional range from diameter 170 – 4000 mm and weights up to 5000 kg.

Ovako develops high-tech steel solutions for, and in cooperation with, its customers in the bearing, transport and manufacturing industries. Our steel makes our customers' end products more resilient and extends their useful life, ultimately resulting in smarter, more energy-efficient and more environmentally-friendly products.

Our production is based on recycled scrap and includes steel in the form of bar, tube, rings and pre-components. Ovako has around 2,700 employees in more than 30 countries. Ovako is a subsidiary of Sanyo Special Steel and a member of Nippon Steel Corporation group, one of the largest steel producers in the world with more than 100,000 employees globally.

For more information, please visit us at www.ovako.com, www.nipponsteel.com, and www.nipponsteel.com,

CONTACT US

www.ovako.com/en/contact/



